



{Hand Carry/Portable}

# Generators

1100 - 2500 - 3000 Maximum Wattage

These compact generators pack a lot of power! The NEW larger fuel tank model permits extended-run times for optimized operational efficiency.



Large low-tone mufflers to reduce noise to lowest level possible



GEN-1100-OMSO



GEN-3000-1MH0

Easy-access and protected control panel with magnetic circuit breaker and GFCI-protected receptacle



Heavy-duty wraparound frame with 1-inch powder coated steel tubing (2500- & 3000-watt models)

**Additional Features:**

- ✓ Low oil shutdown engine
- ✓ Brushless 120V alternator
- ✓ Fuel shutoff valve
- ✓ USDA/USFS-approved spark arrestors
- ✓ Circuit breaker protected
- ✓ Meets CARB & EPA emission standards

**2500- & 3000-Watt Additional Features:**

- ✓ Angled isolator design features four (4) neoprene isolators
- ✓ Low profile, compact design
- ✓ Large fuel tank capacity for extended run time (GEN-3000-1MH0)
- ✓ Heavy-duty industrial air cleaners hold up under the dustiest conditions

**1100-Watt Additional Features:**

- ✓ Battery charging
- ✓ Optimum cooling system and silent muffler provide quiet operation
- ✓ Easy-grip frame design maximizes ease of handling
- ✓ Unique soundproof panels reduce noise
- ✓ Removable side panels for easy maintenance



GFCI 5-20R

## Specifications:

Model #	GEN-1100-OMSO	GEN-2500-OMSO	GEN-3000-OMHO	GEN-3000-1MH0
Max. AC output	1,100 watts	2,500 watts	3,000 watts	3,000 watts
Rated AC output	900 watts	2,200 watts	2,450 watts	2,450 watts
HP/Displacement	2.0/86 cc	4.5/126 cc	5.5/163 cc	5.5/163 cc
Engine	Subaru OHV	Subaru OHC	Honda OHV	Honda OHV
Frequency/Voltage	60Hz/120V	60Hz/120V	60Hz/120V	60Hz/120V
Max. amps (120V)	9.2	20.8	25.0	25.0
Cont. amps (120V)	7.5	18.3	20.4	20.4
Receptacle	120V, 20A GFCI duplex	120V, 20A GFCI duplex	120V, 20A GFCI duplex	120V, 20A GFCI duplex
Main circuit breaker	Electronic circuit protection	20A push-button	20A push-button	20A push-button
Rated speed	3,600 RPM	3,600 RPM	3,600 RPM	3,600 RPM
Decibel rating	59.0	72.4	74.8	74.8
Fuel capacity	0.93 gallon	0.70 gallon	1.0 gallon	2.6 gallon
Run time (at full load)	3.5 hours	2.0 hours	2.7 hours	7.4 hours
Dim. (LxWxH)	19.3in.x11.6in.x17.5in.	25.7in.x17in.x16in.	25.7in.x17in.x16in.	25in.x18in.x18in.
Shipping weight	64 lbs.	125 lbs.	125 lbs.	125 lbs.
Net weight	45.2 lbs.	111 lbs.	111 lbs.	111 lbs.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.



CSA Certified:  
GEN-2500-OMSO  
GEN-3000-OMHO  
GEN-3000-1MH0

33919 Hwy 99 E  
Tangent, OR 97389  
1-800-835-1328