

## Generators

4000 - 5000 Maximum Wattage

The low profile, compact design is an excellent choice for any industrial application.



GEN-4000-0MHO



GEN-5000-0MSO shown with optional lifting hook (AW-5090-0003)

### Additional Features:

- ✓ Low oil shutdown engine
- ✓ Brushless 120V/240V alternator
- ✓ Fuel shutoff valve
- ✓ Easy-to-read fuel gauge
- ✓ Full power switch
- ✓ Angled isolator design features four (4) neoprene isolators
- ✓ USDA/USFS-approved spark arrestors
- ✓ Circuit breaker protected
- ✓ Meets CARB and EPA emission standards
- ✓ Low profile, compact design
- ✓ Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- ✓ Heavy-duty industrial air cleaners hold up under the dustiest conditions



Lifting hook folds down and out of the way when not in use.



Large low-tone mufflers to reduce noise to lowest levels possible

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles



Heavy-duty wraparound frame with 1-inch powder coated steel tubing

### Specifications:

Model #	GEN-4000-0MHO	GEN-4000-0MSO	GEN-5000-0MSO
Max. AC output	4,000 watts	4,000 watts	5,000 watts
Rated AC output	3,500 watts	3,500 watts	4,400 watts
HP/Displacement	8.0/242 cc	7.0/211 cc	9.0/265 cc
Engine	Honda OHV	Subaru OHC	Subaru OHC
Frequency/Voltage	60Hz/120V/240V	60Hz/120V/240V	60Hz/120V/240V
Max. amps (120V/240V)	33.3/16.7	33.3/16.7	41.7/20.8
Cont. amps (120V/240V)	29.2/14.6	29.2/14.6	36.7/18.3
Receptacles	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock
Circuit breakers	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole
Rated speed	3,600 RPM	3,600 RPM	3,600 RPM
Decibel rating	75.7	74.0	73.8
Fuel capacity	5.7 gallon	5.7 gallon	5.7 gallon
Run time (at full load)	9.3 hours	9.3 hours	6.8 hours
Dim. (LxWxH)	29in.x19.75in.x22.5in.	29in.x19.75in.x22.5in.	29in.x19.75in.x22.5in.
Shipping weight	164 lbs.	168 lbs.	198 lbs.
Net weight	142 lbs.	146 lbs.	176 lbs.

Noise level tested at seven meter (75% load). Rating represents minimum noise level rating.

### Options:

- 32-0915 **RV Generator Adapter** - 30A/125V female/male; use to connect RV cordsets to 30A generators
- AW-5090-0003 **Lifting hook** - For easier portability, folds down and out of the way when not in use
- AW-5740-0003 **Wheel kit** - For easier mobility, pneumatic tires with tubes, rubber gripped handles
- GX-0004 **Hour meter** - Displays number of hours the unit has been in operation

Model #	32-0915	AW-5090-0003	AW-5740-0003	GX-0004
All Models	●	●	●	●



GFCI 5-20R



L14-20R  
125/250V



L5-30R  
125 VAC

33919 Hwy 99 E  
Tangent, OR 97389  
1-800-835-1328