

Generators

6000 - 7500 - 8000 Maximum Wattage

This unit is well-suited for the serious contractor with multiple voltage application requirements and additional power needs.



GEN-7500-OMHO




GEN-6000-OMSE shown with electric start and optional wheel kit (AW-5740-0004)



GFCI 5-20R



15-30R
125 VAC



115-250V

Large low-tone mufflers to reduce noise to lowest level possible

Easy-access and protected control panel with magnetic circuit breaker and GFCI-protected receptacle

Heavy-duty wraparound frame with 1-inch powder coated steel tubing

Additional Features:

- ✓ Low oil engine shutdown
- ✓ Electric start available (battery included)
- ✓ Brushless 120V/240V alternator
- ✓ Fuel shutoff valve
- ✓ Easy-to-read fuel gauge
- ✓ Voltmeter/hour meter
- ✓ Idle control
- ✓ Angled isolator design features four (4) neoprene isolators
- ✓ USDA/USFS-approved spark arrestors
- ✓ Circuit breaker protected
- ✓ Meets CARB and EPA emission standards
- ✓ Low profile, compact design
- ✓ Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- ✓ Heavy-duty industrial air cleaners hold up under the dustiest conditions

Specifications:

Model #	GEN-6000-OMHO*	GEN-6000-OMSO*	GEN-7500-OMHO*	GEN-8000-OMSO*
Max. AC output	6,000 watts	6,000 watts	7,500 watts	8,000 watts
Rated AC output	5,000 watts	5,000 watts	6,500 watts	6,900 watts
HP/Displacement	13.0/389 cc	13.5/404 cc	13.0/389 cc	13.5/404 cc
Engine	Honda OHV	Subaru OHV	Honda OHV	Subaru OHV
Frequency/Voltage	60Hz/120V/240V	60Hz/120V/240V	60Hz/120V/240V	60Hz/120V/240V
Max. amps (120V/240V)	50.0/25.0	50.0/25.0	62.5/31.25	66.7/33.3
Cont. amps (120V/240V)	41.7/20.8	41.7/20.8	54.2/27.1	57.5/28.75
Receptacles	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock
Circuit breakers	(2) 20A toggle circuit breaker, single pole (2) 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole (2) 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole
Rated speed	3,600 RPM	3,600 RPM	3,600 RPM	3,600 RPM
Decibel rating	77.1	77.4	80.0	78.2
Fuel capacity	7.3 gallon	7.3 gallon	7.3 gallon	7.3 gallon
Run time (at full load)	8.0 hours	7.9 hours	6.9 hours	6.7 hours
Dim. (LxWxH)	29in.x24.4in.x22.5in.	29in.x24.4in.x22.5in.	29in.x24.4in.x22.5in.	29in.x24.4in.x22.5in.
Shipping weight	232 lbs.	233 lbs.	255 lbs.	245 lbs.
Net weight	210 lbs.	211 lbs.	233 lbs.	223 lbs.

*Available with electric start - battery included.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Options:

32-0915	RV Generator Adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators
AW-5090-0004	Lifting hook - For easier portability, folds down and out of the way when not in use
AW-5740-0004	Wheel kit - For easier mobility, pneumatic tires with tubes, rubber gripped handles



Model #	32-0915	AW-5090-0004	AW-5740-0004
All Models	●	●	●

33919 Hwy 99 E
Tangent, OR 97389
1-800-835-1328